

The emergency temporary glass replacement solution

WindowGuard™

Following the breaking of vehicle glass, WindowGuard™ protects the interior until permanent replacement glass is installed. It's quick, economical and effective. Constructed of a clear, flexible, self-adhesive film, WindowGuard™ is perforated every 91 cm to make installation fast and easy.

The special no-residue adhesive makes WindowGuard™ strong enough for highway speeds and yet it still peels clean upon removal. No need for tape or messy cleanup! Extra clear material provides good visibility.

For more information contact your local Saint-Gobain Autover representative.

Far less expensive and faster to install than plexiglass and other materials, WindowGuard™ meets several needs:

- If replacement glass is not immediately available, WindowGuard™ enables owner to drive vehicle while waiting for permanent replacement
- If vehicle needs to be stored outside awaiting replacement or if emergency roadside service is needed which involves broken glass, WindowGuard™ protects the interior until the replacement glass is installed
- Takes just minutes to install
- Costs far less than cut-out plastic inserts
- Extra clear for good visibility
- Stays on vehicle during even high speed driving, yet peels clean
- Perforated roll for quick installation
- No need for cutting tools

Autover No.	Description
920 113 0500	91 cm x 18.3 m (perforated per 91 cm) per roll

Windowguard™ is a temporary repair film for broken automotive glass

- Protects vehicle interior from weather damage
- Takes minutes to install
- Easy application from perforated roll
- Leaves no residue and is weather proof
- Clear film for good visibility
- Secure fix - will not detach at high speeds



Installation instructions

Apply to a clean and dry surface!
If WindowGuard™ is being applied on a door that will need to be opened repeatedly, open the door prior to installation so that you do not seal the door shut. Then start the application on the door panel just above the door handle (keeping the handle accessible), rolling the material upwards, then folding it over the top side of the door frame. The film may be trimmed if desired. Gently rub down WindowGuard™ to ensure secure seal, then gently close the door (WindowGuard™ provides a tight seal and will pop up if the door is closed too rapidly). Alternatively, if the broken glass is from a door that won't need to be opened, you can simply apply WindowGuard™ on the vehicle exterior in the most convenient manner that covers the open area. Rub down once in place to ensure a secure seal. WindowGuard™ will peel easily with no need for cleanup. In either case, if a tight seal is not achievable due to attachments and curvatures of the vehicle body, the no-residue Moulding Retention Tape (Autover no. 920 113 0000) may be used to firmly seal critical edges of WindowGuard™ to car body.